


WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5mm STEREO JACK,NICKEL PLATED SHELL AND P2:3.5mm STEREO JACK,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20M  $\Omega$   
INSULATION RESISTANC: 20M  $\Omega$ WITHSTAND VOLTAGE AC:150V DC:250V  
CURRENT RATING AC:100V/0.5A DC:200V/0.5A
5. OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
6. OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.



TOLERANCE			Tri-Net Technology, Inc.			
INCHES	M/M		http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE		REV   A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	TNT-S101-0268
DRAWN BY			DATE	03/22/05		
CHECK BY			TITLE ø3.5mm STEREO JACK TO JACK			
APPD BY			PART NO. 127-35SF-35SF			