



WIRE		LIST	
P1	P2	P2	P3
1	1	1	1
2	2	2	2
3	3	3	3

REMARK:

- CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHART REGULATION. APPEARANCE: EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- P1: 3.5MM STEREO PLUG, GOLD PLATED SHELL, GOLD PLATED CONTACT AND P2 P3: 3.5MM STEREO JACK, GOLD PLATED SHELL, GOLD PLATED CONTACT.
- ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE: 20M  $\Omega$   
INSULATION RESISTANC: 2M  $\Omega$  WITHSTAND VOLTAGE AC: 100V DC: 150V,  
CURRENT RATING AC: 100V/0.5A DC: 150V/1A
- OPERATING TEMPERATURE -30°C - +60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- OVERMOLD COLOR IS BALCK AND MATERIAL IS PVC PLASTIC.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc.	
.X	.015			.30		http://www.trinetusa.com	
.XX	.010			.10		SCALE	NONE
.XXX	.005			.05		UNIT	MM
DRAWN BY						SHEET	1/2
						DATE	03/22/05
CHECK BY						DWG NO. TNT-S101-0276	
						TITLE	
APPD BY						PART NO. 127-35SM-35SF2	
						TITLE	
						Ø3.5mm STEREO PLUG TO 2*Ø3.5mm STEREO JACK	