



WIRE		LIST	
P1			P2
1	_____		1
2	_____		2
3	_____		3

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5MM STEREO PLUG,GOLD PLATED SHELL,GOLD PLATED CONTACT, AND P2:6.35MM STEREO Jack,GOLD PLATED SHELL,GOLD PLATED CONTACT.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.5Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:10M Ω
INSULATION RESISTANC: 20M Ω WITHSTAND VOLTAGE AC:150V DC:250V,
CURRENT RATING AC:100V/0.5A DC:150V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL PVC PLASTIC.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc. http://www.trinetusa.com				
.X	.015			.30	SCALE	NONE		REV	A	
.XX	.010			.10	UNIT	MM				
.XXX	.005			.05	SHEET	1/2	DWG NO.	TNT-S101-0274		
DRAWN BY					DATE	03/22/05	PART NO. 127-35SM-63SF			
CHECK BY					TITLE ø3.5mm STEREO PLUG ø6.3mm STEREO JACK					
APPD BY										