

WIRE		LIST	
P2		P1	P3
1	CENTER	1	
		2	CENTER
2	SHELL	3	SHELL
			1
			2

REMARK:

1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.

2.P1:3.5mm STEREO PLUG,GOLD PLATED SHELL AND P2 P3:RCA JACK.GOLD PLATED SHELL.

3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.

4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:20M Ω


INSULATION RESISTANC: 2MΩWITHSTAND VOLTAGE AC:100V DC:150V

CURRENT RATING AC: 100V/0.5A DC:150V/1A

5. OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.

6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc. http://www.trinetusa.com				
.X	.015		.30	SCALE	NONE		REV	A	DWG NO.	
.XX	.010		.10	UNIT	MM					
.XXX	.005		.05	SHEET	1/2					
DRAWN BY				DATE	03/22/05	TNT-S101-0278				
CHECK BY				TITLE ø3.5mm STEREO PLUG TO 2RCA/F						
APPD BY				PART NO. 127-35SM-RCAF2						