



WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:6.35MM STEREO PLUG,GOLD PLATED SHELL AND P2:3.5MM STEREO JACK,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:10M Ω
INSULATION RESISTANC: 20MΩWITHSTAND VOLTAGE AC:150V DC:250V
CURRENT RATING AC: 100V/0.5A DC:150V/1A
- 5.OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
6. OVMOLD COLOR IS BLACK AND MATERIAL IS PVC .



TOLERANCE			TNT Tri-Net Technology, Inc.			
INCHES	M/M		http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE	⊕	REV A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	TNT-S101-0277
DRAWN BY			DATE	03/22/05	TITLE	
CHECK BY			ø3.5mm STEREO JACK ø6.3mm STEREO PLUG			
APPD BY			PART NO. 127-63SM-35SF			