



WIRE		LIST	
P1		P2	
1	—————	1	CENTER
2	—————	2	OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1: BNC FEMALE,NICKEL PLATED SHELL,GOLD FLASH CONTACTS AND P2:FEMALE,NICKEL PLATED SHELL,GOLD FLASH CONTACTS.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:20M Ω
INSULATION RESISTANC:20M Ω WITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
- 5.OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO OVMOLD.



TOLERANCE			Tri-Net Technology, Inc.	
INCHES	M/M	http://www.trinetusa.com		
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	SHEET	1/2
			DATE	03/22/05
			DWG NO. TNT-S101-0280	
DRAWN BY			TITLE BNC/F TO F CONNECTOR/F	
CHECK BY			PART NO. 127-BNCF-FF	
APPD BY				