



WIRE LIST

P1		P2	
1	_____	1	CENTER
2	_____	2	OUTTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:F CONNECTOR MALE,NICKEL PLATED SHELL,GOLD PLATED CONTACTS, AND P2:BNC FEMALE,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3KG TO 12KG.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20M
INSULATION RESISTANC: 20M WITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
- 5.OPERATING TEMPERATURE-30°C---+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.ON OVERMOLD.



TOLERANCE INCHES		M/M	TNT Tri-Net Technology, Inc. http://www.trinetusa.com				
.X	.015	.30	SCALE	NONE		REV	A
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET 1/1		DWG NO.		
DRAWN BY			DATE 03/22/05		TNT-S101-0286		
CHECK BY			TITLE F CONNECTOR/M TO BNC/F				
APPD BY			PART NO. 127-BNCF-FM				