



WIRE LIST

P1		P2	
1	—————	1	CENTER
2	—————	2	OUTER

REMARK:

1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.

2.P1: BNC FEMALE,NICKEL PLATED SHELL,NICKEL FLASH CONTACTS AND P2:RCA MALE,NICKEL PLATED SHELL,NICKEL FLASH CONTACTS.

3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.

4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20MΩ  
INSULATION RESISTANC:20MΩ WITHSTAND VOLTAGE AC:200V DC:250V  
CURRENT RATING AC:100V/0.5A DC:150V/1A

5.OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.

6.NO OVMOLD.



TOLERANCE			Tri-Net Technology, Inc.					
INCHES	M	M	<a href="http://www.trinetusa.com">http://www.trinetusa.com</a>					
.X	.015	.30	SCALE	NONE		REV	A	
.XX	.010	.10	UNIT	MM				
.XXX	.005	.05	SHEET	1/2				
DRAWN BY			DATE	04/02/05	DWG NO.	TNT-S101-0295		
CHECK BY			TITLE					BNC/F TO RCA/M
APPD BY			PART NO.					127-BNCF-RCAM