



P1		WIRE	LIST	P2	
1	_____		1	_____	CENTER
2	_____		2	_____	OUTER

REMARK:

- CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHART REGULATION. APPEARANCE: EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- P1: BNC MALE, NICKEL PLATED SHELL, GOLD PLATED CONTACTS AND P2: F CONNECTOR FEMALE, NICKEL PLATED SHELL, GOLD PLATED CONTACTS.
- ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE: 20M Ω
INSULATION RESISTANC: 20M Ω WITHSTAND VOLTAGE AC: 200V DC: 250V
CURRENT RATING AC: 100V/0.5A DC: 150V/1A.
- OPERATING TEMPERATURE -30°C - +60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- NO OVMOLD.



TOLERANCE			Tri-Net Technology, Inc.				
INCHES	M/M		http://www.trinetusa.com				
.X	.015	.30	SCALE	NONE		REV	A
.XX	.010	.10	UNIT	MM		DWG NO.	TNT-S101-0272
.XXX	.005	.05	SHEET	1/2	DATE	03/22/05	
DRAWN BY			TITLE		BNC/M TO F CONNECTOR/F, SCREW ON TYPE		
CHECK BY			PART NO.		127-BNCM-FF-T		
APPD BY							