



WIRE LIST

P1		P2	
1	_____	1	CENTER
2	_____	2	OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:F CONNECTOR MALE,NICKEL PLATED SHELL,NICKEL PLATED CONTACTS,AND P2:BNC MALE,NICKEL PLATED SHELL,NICKEL PLATED CONTACTS.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3KG TO 12KG.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:20M Ω
INSULATION RESISTANC: 20M ΩWITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
5. OPERATING TEMPERATURE-30°C---+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO OVERMOLD.



TOLERANCE			Tri-Net Technology, Inc.				
INCHES	M/M		http://www.trinetusa.com				
.X	.015	.30	SCALE	NONE		REV	A
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET	1/2	DWG NO.		
DRAWN BY			DATE	03/22/05	TNT-S101-0288		
CHECK BY			TITLE				
APPD BY			BNC/M TO F CONNECTOR/M				
			PART NO. 127-BNCM-FM				