



WIRE LIST

P1		P2	
1	_____	1	CENTER
2	_____	2	OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:BNC MALE,NICKEL PLATED SHELL,NICKEL PLATED CONTACTS AND P2:RCA FEMALE,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:30M Ω
INSULATION RESISTANC: 50MΩWITHSTAND VOLTAGE AC:150V DC:300V
CURRENT RATING AC:150V/0.5A DC:250V/1A
- 5.OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO MOLDING.



TOLERANCE			TNT Tri-Net Technology, Inc.			
INCHES	M	M	http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE		A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	
DRAWN BY			DATE	03/22/05	TNT-S101-0282	
CHECK BY			TITLE BNC/M TO RCA/F			
APPD BY			PART NO. 127-BNCM-RCAF			