



WIRE LIST

P1		P2
1	_____	1
2	_____	2

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5MM MONO MALE,NICKEL PLATED SHELL AND P2:F CONNECTOR FEMALE,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- 4.ELECTRONIC CHARACTERISTICS:CONTACT RESISTANCE:20M Ω
INSULATION RESISTANC:20M ΩWITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
5. OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO OVMOLD.



TOLERANCE		M/M		TNT Tri-Net Technology, Inc.				
INCHES				http://www.trinetusa.com				
.X	.015	.30		SCALE	NONE		REV	A
.XX	.010	.10		UNIT	MM			
.XXX	.005	.05		SHEET	1/2	DWG NO. TNT-S101-0285		
				DATE	03/22/05			
DRAWN BY				TITLE		F CONNECTOR/F TO 3.5MM MONO/M		
CHECK BY				PART NO.		127-FF-35MM		
APPD BY								