



P1		P2	
WIRE		LIST	
1	_____	1	_____ CENTER
2	_____	2	_____ OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:RCA PLUG,GOLD PLATED SHELL,GOLD PLATED CONTACTS,AND P2: F CONNECTOR JACK,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5KG TO 2.0KG
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:50M Ω
INSULATION RESISTANC: 20MΩWITHSTAND VOLTAGE AC:250V DC:300V
CURRENT RATING AC:100V/0.5A DC:250V/1A
5. OPERATING TEMPERATURE-30°C-----+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
6. NO OVERMOLD.



TOLERANCE			Tri-Net Technology, Inc.	
INCHES	M/M		http://www.trinetusa.com	
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05		
DRAWN BY		SHEET	1/2	DWG NO.
		DATE	03/22/05	TNT-S101-0287
CHECK BY		TITLE		
		RCA/M TO F CONNECTOR/F		
APPD BY		PART NO.		
		127-FF-RCAM		