



WIRE LIST	
P1	P2
1	1
2	2
3	3
4	4
SHELL	SHELL

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1 AND P2:MD 4PIN FEMALE,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- 4.ELECTRONIC CHARCTERISTICS:CONTACT RESISTANCE:20MΩ
INSULATION RESISTANC:20MΩ WITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
5. OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BALCK AND MATERIAL IS PVC PLASTIC.



TOLERANCE			Tri-Net Technology, Inc.			
INCHES	M/M		http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE	REV	B
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	DRAWN BY Jeamous		DWG NO. TNT-S101-0293	
			CHECK BY	TITLE MD4/F TO MD4/F		
			APPD BY	PART NO. 127-MD4F-MD4F		