



WIRE LIST	
P1	P2
2	SHELL
3	CENTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:MINI DIN 4P FEMALE,GOLD PLATED SHELL AND P2: RCA FEMALE,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:10M Ω
INSULATION RESISTANC: 5M ΩWITHSTAND VOLTAGE AC:100V DC:250V,
CURRENT RATING AC: 100V/0.3A DC:200V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMAL COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.



TOLERANCE		INCHES		M/M		Tri-Net Technology, Inc. http://www.trinetusa.com			
.X	.015			.30	SCALE	NONE		REV A	
.XX	.010			.10	UNIT	MM			
.XXX	.005			.05	SHEET	1/2			
DRAWN BY					DATE	03/22/05		DWG NO.	TNT-S101-0273
CHECK BY					TITLE RCA/F TO MD4/F ADAPTER				
APPD BY					PART NO. 127-MD4F-RCAF				