



WIRE LIST	
P1	P2
2	2
3	1

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:4 PIN MINI DIN FEMALE,GOLD PLATED SHELL AND P2: RCA PLUG,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:10M Ω
INSULATION RESISTANC: 5M Ω WITHSTAND VOLTAGE AC:100V DC:250V,
CURRENT RATING AC: 100V/0.3A DC:200V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.



TOLERANCE			Tri-Net Technology, Inc.	
INCHES	M/M	http://www.trinetusa.com		
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	REV A	
DRAWN BY			SHEET	1/2
CHECK BY			DATE	03/22/05
APPD BY			DWG NO. TNT-S101-0270	
			TITLE	
			RCA/M TO MD4/F ADAPTER	
			PART NO.	
			127-MD4F-RCAM	