



WIRE		LIST	
P1			P2
1	_____		1
2	_____		2

REMARK:

- CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHART REGULATION. APPEARANCE: EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- P1: RCA JACK, NICKEL PLATED SHELL, AND P2: 3.5MM MONO PLUG, NICKEL PLATED SHELL.
- ADAPTER INSERION EXTRSCION: FORLE 0.5KG TO 2.0KG
- ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE: 50M Ω
INSULATION RESISTANC: 20M Ω WITHSTAND VOLTAGE AC: 250V DC: 300V
CURRENT RATING AC: 100V/0.5A DC: 250V/1A
- OPERATING TEMPERATURE -30°C ---- +60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- NO OVMOLD.



TOLERANCE		M/M		TNT Tri-Net Technology, Inc.		
INCHES				http://www.trinetusa.com		
.X	.015	.30	SCALE	NONE		REV A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	TNT-S101-0294
DRAWN BY			DATE	03/22/05	TITLE	
CHECK BY			RCA/F TO F 3.5mm Mono Plug Male			
APPD BY			PART NO. 127-RCAF-35MM			