



WIRE LIST

P1		P2
1	CENTER	1
2	SHELL	2

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1 AND P2:RCA JACK,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20M Ω
INSULATION RESISTANC: 2M Ω WITHSTAND VOLTAGE AC:200V DC:250V,
CURRENT RATING AC: 100V/0.5A DC:150V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PLASTIC.



TOLERANCE		INCHES		M/M		TNT Tri-Net Technology, Inc. http://www.trinetusa.com				
.X	.015			.30	SCALE	NONE			REV	A
.XX	.010			.10	UNIT	MM				
.XXX	.005			.05	SHEET	1/2		DWG NO.		
DRAWN BY					DATE	03/22/05		TNT-S101-0269		
CHECK BY					TITLE RCA/F TO RCA/F ADAPTER					
APPD BY					PART NO. 127-RCAF-RCAF					