



REMARK:

1. CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARACTERIZATION APPEARANCE: EVERY PART SHOULD BE FINISHED NOT TO DILAPIDATION, CRACK AND BAD PLATING.
2. P1: RCA PLUG, GOLD PLATED SHELL AND P2 P5: RCA JACK, GOLD PLATED SHELL.
3. ADAPTER INSERION EXTRSION: FOR LZ 0.5Kg TO 2.0Kg.
4. ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE: 20M
INSULATION RESISTANCE: 2M WITH STAND VOLTAGE Δ0: 100V DC: 150V
CURRENT RATING Δ0: 10

**OHS
COMPLIANT**

TOLERANCE		M/M		Tri-Net Technology, Inc. http://www.trinetusa.com		
INCHES						
.X	.015	.30	SCALE	NONE	REV A	
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	
DRAWN BY			DATE	03/22/05		
CHECK BY			TITLE	RCA/M TO 2RCA/F ADAPTER		
APPD BY			PART NO.	127-RCAM-RCAF2		