



NOTE:

1. CABLE: UL2919 28AWG*2COAX(UL1354 75ohm)+AL-FOIL SHIELDED WITH DRAIN WIRE +BRAID SHIELDED+BLACK PVC JACKET. OD:7.0±0.15mm.
2. CONNECTOR: P1 & P2: MINI DIN 4PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
4. ALL HOOD: MOLDED BLACK PVC.
5. PACKING: EACH CABLE IN A TNT PRINTED POLY-BAG.
BAR CODE LABEL TO BE STAMPED ON POLYBAG.

PIN OUT



SHELL ——— SHELL(BRAID)



CHART 1:

P/N	**	xx	L	T
C28-MDIN4-MM-03	3	03	914	±30
C28-MDIN4-MM-06	6	06	1829	±51
C28-MDIN4-MM-10	10	10	3048	±51
C28-MDIN4-MM-12	12	12	3658	±51
C28-MDIN4-MM-25	25	25	7620	+152/-51
C28-MDIN4-MM-50	50	50	15240	+305/-152
C28-MDIN4-MM-75	75	75	22860	+305/-152
C28-MDIN4-MM-80	80	80	24384	+305/-152
C28-MDIN4-MM-100	100	100	30480	+305/-152

TOLERANCE			Tri-Net Technology, Inc. http://www.trinetusa.com	
INCHES		M/M		
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	SHEET	1/1
DRAWN BY			DATE	01/31/04
			DWG NO. TNT-S101-0171	
CHECK BY			TITLE	
			MD4/M TO MD4/M	
APPD BY			PART NO.	
			C28-MDIN4-MM-XX	

