



P/N	FT	L	T
C30-5RM-5RM-03	3	914mm	±30mm
C30-5RM-5RM-06	6	1829mm	±51mm
C30-5RM-5RM-12	12	3657mm	+152/-51mm

NOTE:
 — RCA HOT
 — RCA GND

- ① NOU-UL [1C*26AWG(13/0.12)+AL/MY+SPIRAL+PVC JACKET BLACK(TNT-BK)]*3F
OD=6.0*6.0*6.0±0.15MM
- ② P1 & P2 & P3 & P4 & P5 & P6 & P7 & P8 & P9 & P10 RCA PLUG,SHELL GOLD
PLATED 3u", INSULATION WHITE.
- ③ MOLD 45PVC BLACK(TNT-BK).
- ④ COLOR RING:60P PVC.
- 5. 100% ELECTRICAL TESTING.
- 6. MOLD NO:TNT-RCA-02.



TOLERANCE		INCHES		M/M		Tri-Net Technology, Inc. http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE	REV A	DWG NO.	TNT-S101-0155	TITLE	A/V CABLE 5RCA TO 5RCA
.XX	.010	.10	UNIT	MM					
.XXX	.005	.05	SHEET	1/2	DATE	05/12/05	PART NO.	C30-5RM-5RM-XX	
DRAWN BY		WENDI							
CHECK BY									
APPD BY									