



P/N	FT	L	T
C30-TL-03	3	914mm	±30mm
C30-TL-06	6	1829mm	±51mm
C30-TL-12	12	3657mm	+152/-51mm

PIN OUT:



### Specification:

- 1 CONN P1,P2: TOS-LINK CONNECTOR PBT+30%FUNICLE,SHEER DUST CAP.PVC MOLDING.
- 2 CABLE: PLASTIC OPTICAL CORE  $\phi$ 1.0mm PMMA+JACKET(TNT-BK), $\phi$ 5.0mm.
- 3 Insertion Loss: <2.0dB (Test by 660±30nm LED light source/power meter)
- 4 Temperature test: <3.5dB (Test by -25 to 70°C for 30 minutes)



TOLERANCE INCHES		M/M	<b>TNT</b> Tri-Net Technology, Inc. <a href="http://www.trinetusa.com">http://www.trinetusa.com</a>					
.X	.015	.30	SCALE	NONE		REV	A	
.XX	.010	.10	UNIT	MM				
.XXX	.005	.05	SHEET	1/2	DWG NO.			
DRAWN BY			WENDI	DATE	05/12/05	TNT-S101-0162		
CHECK BY			TITLE					TOSLINK TO TOSLINK
APPD BY			PART NO.					C30-TL-XX