


PIN OUT:



P/N	FT	L	T
C30-TLSV-03	3	914mm	±30mm
C30-TLSV-06	6	1829mm	±51mm
C30-TLSV-12	12	3657mm	+152/-51mm

Specification:

- 1 CONN P1,P3: TOS-LINK CONNECTOR,SHEER DUST CAP,PVC MOLDING.
- 2 CONN P2,P4: MINI DIN 4PIN GOLD PLATED.4G TYPE SHELL.
- 3 CABLE: S-VIDEO CABLE + PLASTIC OPTICAL CABLE.BLACK JACKET,ø5.0*5.0mm.
- 4 TESTING: Insertion Loss<2.0dB (Test by 660±30nm LED light source/power meter)
Temperature test IL<3.5dB (Test by -25 to 70°C for 30 minutes)
100% ELECTRICAL TESTING.



TOLERANCE		M/M		TNT Tri-Net Technology, Inc.				
INCHES				http://www.trinetusa.com				
.X	.015	.30		SCALE	NONE		REV	A
.XX	.010	.10		UNIT	MM			
.XXX	.005	.05						
DRAWN BY		WENDI		SHEET	1/2	DWG NO.		
CHECK BY				DATE		05/12/05		
APPD BY				TITLE		TOSLINK+S-VIDEO TO TOSLINK+S-VIDEO		
				PART NO.		C30-TLSV-XX		