



APPROVED BY \_\_\_\_\_  
 COMPANY: \_\_\_\_\_  
 PURCHASING/ENGINEER: \_\_\_\_\_  
 DATE: \_\_\_\_\_

L	T
L ≤ 3FT	+50/-50mm
3FT < L ≤ 15FT	+100/-100mm
15FT < L ≤ 30FT	+150/-150mm
L > 30FT	+200/-200mm

- NOTE:
- NOU-UL [1C\*26AWG(13/0.12)+AL/MY+SPIRAL+PVC JACKET BLACK]\*4F  
OD=6.0\*6.0\*6.0\*6.0\*6.0±0.15MM, 75 Ohm.
  - P1 & P2 & P3 & P4 & P5 & P6 & P7 & P8 RCA PLUG,  
SHELL GOLD PLATED 3u", INSULATION WHITE.
  - MOLD 45PVC BLACK.
  - COLOR RING:90P PVC.
  - 100% ELECTRICAL TESTING.
  - MOLD NO:RCA-02,RCA-CV.



A	INITIAL RELEASE		08/17/06		
REV	DESCRIPTION OF CHANGE		DATE		
TOLERANCE INCHES		M/M	Tri-Net Technology, Inc. <a href="http://www.trinetusa.com">http://www.trinetusa.com</a>		
.X	.015	.30			
.XX	.010	.10			
.XXX	.005	.05	SCALE	NONE	REV A
DRAWN BY		UNIT	MM		
CHECK BY		SHEET	1/1	DWG NO.	
APPD BY		DATE	1/19/08	TITLE	
			A/V CABLE 4RCA TO 4RCA		
			PART NO. C30-4RM-4RM-XX		