



P/N	FT	T(INCH)
EZ02-A-15	15	+6/-2
EZ02-A-25	25	+6/-2
EZ02-A-35	35	+6/-2
EZ02-A-50	50	+6/-2
EZ02-A-75	75	+12/-6
EZ02-A-100	100	+12/-6
EZ02-A-125	125	+12/-6
EZ02-A-150	150	+12/-6



NOTE:

1. CABLE: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, UL1354) + (24AWG X 8C)], AL-FOIL AND BRAID SHIELDED WITH DRAIN WIRE, UL2919, BLACK PVC JACKET, SLOT $\phi 8.0 \pm 0.15$ mm.CMP RATED.
2. CONNECTOR: P1 & P2: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL.
3. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
4. DIN CAP:BRASS,NICKEL PLATED.
5. ALL HOOD: MOLDED GREEN(GN02) PVC.
6. TESTING: 100% ELECTRICAL TEST .
7. PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
8. MOLD NO.: D14F-N01, D14F-02.



A	INITIAL RELEASE		11/22/07	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES		M/M	Tri-Net Technology, Inc. http://www.trinetusa.com	
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05	SCALE	NONE
			UNIT	MM
DRAWN BY		LUCY	SHEET	1/1
			DATE	11/22/07
CHECK BY		TITLE		
		DIN 14/F TO DIN 14/F		
APPD BY		PART NO.		
		EZ02-A-XX		