



PIN OUT	
P1	P2
1	1
6	6
2	2
7	7
3	3
8	8
4	4
5	5
11	11
12	12
10	10
13	13
14	14
9	9
SHELL	SHELL(DRAIN + BRAID)

1 } RED
 2 } GREEN
 3 } BLUE
 4 BLACK
 5 BROWN
 11 YELLOW
 12 PURPLE
 10 ORANGE
 13 ORANGE/BLACK
 14 BLUE
 9 BLUE/WHITE

NOTE:

- CABLE: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, UL1354) + (24AWG X 4C) + (24AWG X 2PAIRS)], AL-FOIL AND BRAID SHIELDED WITH DRAIN WIRE, UL2919, BLACK PVC JACKET, SLOT ø8.5±0.15mm.
- CONNECTOR: P1: DIN 14P MALE, NICKEL PLATED CONTACTS AND SHELL, LOCKER TYPE.
P2: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL, LONG SCREW THREAD TYPE, WITH HEX NUT.
- METAL FACE PLATE: 1PORT, STAINLESS STEEL, WHITE PAINTED.
- SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
- ALL HOOD: MOLDED GREEN(GN02) PVC.
- TESTING: 100% ELECTRICAL TEST .
- PACKING: EACH CABLE IN A BOX.
- MOLD NO.: D14M-N01, DIN14M-02, D14F-N01, D14F-02.



A	INITIAL RELEASE		11/22/07	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES		M/M	Tri-Net Technology, Inc. http://www.trinetusa.com	
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	REV A	
DRAWN BY	Walt		SHEET	1/1
			DATE	11/22/07
CHECK BY			TITLE	
			DIN 14 M TO DIN 14/F+FACE PLATE	
APPD BY			PART NO.	
			EZ04-D14-FP	