



- NOTE:
- CABLE: (28AWG X 5 COAX, EACH COAX SPIRAL SHIELDED, UL1354, COLOR CODE: RED, GREEN, BLUE, GREY, BLACK), AL-FOIL AND BRAIDSHIELDED WITH DRAIN, UL2919 + CUL IA FT1, BLACK PVC JACKET. $\varnothing 9.0 \pm 0.15\text{mm}$.
 - CONNECTOR: P1: DIN 14P MALE, NICKEL PLATED CONTACTS AND SHELL, LOCKER TYPE.
P2: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL, LONG SCREW THREAD TYPE, WITH HEX NUT.
 - METAL FACE PLATE: 1PORT, STAINLESS STEEL, WHITE PAINTED.
 - SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
 - ALL HOOD: MOLDED ORANGE(OR02) PVC.
 - TESTING: 100% ELECTRICAL TEST .
 - PACKING: EACH CABLE IN A BOX.
 - MOLD NO.: D14M-N01, D14M-02, D14F-N01, D14F-02.



A	INITIAL RELEASE		11/22/07	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE			Tri-Net Technology, Inc. http://www.trinetusa.com	
INCHES				
M/M				
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	REV A	
DRAWN BY	Walt		SHEET	1/1
CHECK BY			DATE	11/22/07
APPD BY			DWG NO.	
TITLE			DIN 14 M TO DIN 14/F+FACE PLATE	
PART NO.			EZ04-D14B-FP	