



PIN OUT

P1	P2 COLOR	P1	P2 COLOR
1	WHITE	10	WHITE
3	BROWN	12	BLUE
2	DRAIN	11	DRAIN
4	WHITE	13	PURPLE
6	RED	14	RED
5	DRAIN	15	YELLOW
7	WHITE	16	ORANGE
9	GREEN	17	BLUE
8	DRAIN	18	GREEN
		19	WHITE
		SHELL	SHELL BRAID

NOTE:

- CABLE: UL20276 HDMI 1.3 CABLE, (28#*1P+D+MYLAR+AL)*4C+28#*1P+28#*5C+AB, JACKET: BLACK, OD:6.5MM.
- CONNECTOR: P1: DIN 19P MALE, SOLDER TYPE, TINNED PLATED CONTACTS, INSULATION: BLACK, NICKEL PLATED SHELL.
P2: HDMI 19P FEMALE: BLACK, GOLD PLATED SHELL.
- PLASTIC FACE PLATE: 1PORT, WHITE PLASTIC.
- P1 SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
- HOOD: P1: MOLDED BLACK PVC;P2: MOLDED 25P WHITE(WH05) PVC.
- 100% OPEN AND SHORT TESTING.
- MOLD NO: D14M-N01, D14M-02, HDMI-11, HDMI-N11.



A	INITIAL RELEASE		11/24/08	
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE		Tri-Net Technology, Inc.		
INCHES M/M		http://www.trinetusa.com		
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	REV A	
DRAWN BY	Carl		SHEET	1/1
CHECK BY			DATE	11/24/08
APPD BY			DWG NO.	
TITLE			DIN19M TO HDMI19F+FACE PLATE	
PART NO.			EZ04-HDMI-FP	