

**1875GA Paired - MediaTwist® Enhanced Category 6**

	<p><b>For more information please call</b> <b>1-800-Belden1</b></p> <p><b>Related Documents :</b> <b>MediaTwist Patch Cables.pdf</b></p>
---	--

**Description:**

4 Pair UTP, 350MHz Enhanced Category 6, Riser Rated, 24 AWG Stranded Tinned Copper, Polyolefin Insulation, Bonded Pairs, Flexible PVC Jacket, T568-A Color Rotation

**SUITABLE APPLICATIONS:**

Suitable Applications	Premise Patch Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments
-----------------------	---

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	7x32
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material	PO - Polyolefin
---------------------	-----------------

**Pair Color Code Chart :**

Number	Color	Number	Color
For T568-A Wiring	White/Brown Stripe & Brown		White/Orange Stripe & Orange
	White/Blue Stripe & Blue		White/Green Stripe & Green

**OUTER SHIELD:**

Outer Shield Material	Unshielded
-----------------------	------------

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.365 x .165 in.
--------------------------	-----------------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.

**1875GA Paired - MediaTwist® Enhanced Category 6**

Min. Bend Radius (Install)	0.1 in.
----------------------------	---------

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CMR, UL444
CEC/C(UL) Specification	CMR
IEC Specification	11801 Category 5 Patch
TIA/EIA Specification	568-B.2-1 Category 6 Patch, B.2 Category 5e Horizontal
Other Specification	UL verified to Category 6

**FLAME TEST:**

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**ELECTRICAL CHARACTERISTICS:**

Nom. Mutual Capacitance @ 1 KHz	15.0 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	49.2 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	510 @ 100MHz ns/100 m
Maximum Delay Skew (ns/100m)	25 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

**ELECTRICAL CHARACTERISTICS - PREMISE:**

Premise Cable Electricals Table 1 :	
-------------------------------------	--

**1875GA Paired - MediaTwist® Enhanced Category 6**

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	74.3	72.3	70.3	70.3	20.0	
4	4.1	65.3	63.3	59.2	59.2	23.0	
8	5.8	60.3	58.8	53.0	53.0	24.5	
10	6.5	59.3	57.3	50.8	50.8	25.0	
16	8.2	56.3	54.3	46.0	46.0	25.0	
20	9.3	54.8	52.8	43.5	43.5	25.0	
25	10.4	53.4	51.4	41.0	41.0	24.3	
31.25	11.7	51.9	49.9	38.2	38.2	23.6	
62.5	17.0	47.4	45.4	28.4	28.4	21.5	
100	22.0	44.3	42.3	25	25	21.0	
155	30.2	41.5	39.5	14	14	21.0	
200	34.8	39.8	37.8	10	10	21.0	
250	39.6	38.3	36.3	3	3	18.0	
300	46.7	37.2	34.2	0	0	18.0	
310	47.6	36.9	34.9			18.0	
350	51.1	36.2	34.2			17.0	
400	55.3	35.3	33.3			14.0	
500	63.3	33.8	31.8			14.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	100 ± 15	67.8	64.8
4	100 ± 12	100 ± 15	55.7	52.7
8	100 ± 12	100 ± 15	49.7	46.7
10	100 ± 12	100 ± 15	47.8	44.8
16	100 ± 12	100 ± 8	43.7	40.7
20	100 ± 12	100 ± 8	41.7	38.7
25	100 ± 15	100 ± 8	39.8	36.8
31.25	100 ± 15	100 ± 8	37.9	34.9
62.5	100 ± 15	100 ± 8	31.8	28.8
100	100 ± 15	100 ± 8	27.8	24.8
155	100 ± 15	100 ± 8	23.9	20.9
200	100 ± 15	100 ± 8	21.7	18.7
250	100 ± 20	100 ± 8	19.8	16.8
300	100 ± 20	100 ± 8	18.2	15.2
310	100 ± 20	100 ± 8	17.9	14.9
350	100 ± 22	100 ± 8	16.9	13.9
400	100 ± 32	100 ± 8	15.7	12.7
500	100 ± 32	100 ± 8	13.8	10.8

**NOTES:**

Notes US Patent #'s 5, 606, 151; 5, 734, 126; 5, 763, 823; 5, 821, 467 \*\*Values above 350 MHz are information only

Notes (Cont'd.) RJ-45 Compatible

---

**1875GA Paired - MediaTwist® Enhanced Category 6**

Revision Number: 1      Revision Date: 12-20-2004

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.