

1505F Coax - RG-59/U Type

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	--

Description:

22 AWG stranded (7x29) .031" bare compacted copper conductor, gas-injected foam HDPE insulation, tinned copper double braid shield (95% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	22
Stranding	7x29
Conductor Diameter	.031 in.
Conductor Material	BCC - Bare Compacted Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.145 in.

OUTER SHIELD:

Outer Shield Type	Braid/Braid
-------------------	-------------

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1		Braid	TC - Tinned Copper	94
2		Braid	TC - Tinned Copper	94

Outer Shield % Coverage	98 %
-------------------------	------

Outer Shield Diameter :

Description	Diameter (in.)	Description	Diameter (in.)
Layer 1	.167	Layer 2	.189

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.242 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

1505F Coax - RG-59/U Type

Operating Temperature Range	-35°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	40 lbs/1000 ft.
Max. Recommended Pulling Tension	90 lbs.
Min. Bend Radius (Install)	2.4 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

SWEEP TEST:

Sweep Testing	100% Sweep tested 5 MHz to 3 GHz.
---------------	-----------------------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes - Black Only
Suitability - Aerial	Yes - Black only, when supported by a messenger wire

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	0.094 μ H/ft
Nom. Capacitance Conductor to Shield	17.0 pF/ft
Nominal Velocity of Propagation	80 %
Nominal Delay	1.3 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	12.2 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	2.4 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	3000	15

Nom. Attenuation :

1505F Coax - RG-59/U Type

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.2
	3.6			.5
	5			.6
	7			.73
	10			.9
	67.5			2.4
	71.5			2.5
	88.5			2.8
	100			3.0
	135			3.5
	143			3.6
	180			4.1
	270			5.1
	360			6.0
	540			7.4
	720			8.7
	750			8.9
	1000			10.5
	1500			13.3
	2000			15.7
	2250			16.9
	3000			20.3

Max. Operating Voltage - UL	300 V RMS
Other Electrical Characteristic 1	Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.
Other Electrical Characteristic 2	Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

NOTES:

Notes	Compacted conductor combines impedance uniformity of solid conductors and "nick-resistance" of stranded conductor.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1505F 0041000	#21 GIFHDLDP DBLB PVC	1000	45	YELLOW	C
1505F B591000	#21 GIFHDLDP DBLB PVC	1000	45	BLACK, MATTE	C
1505F G7V1000	#21 GIFHDLDP DBLB PVC	1000	45	RED, MATTE	C
1505F G7W1000	#21 GIFHDLDP DBLB PVC	1000	45	GREEN, MATTE	C
1505F G7X1000	#21 GIFHDLDP DBLB PVC	1000	45	BLUE, MATTE	C
1505F G7Y1000	#21 GIFHDLDP DBLB PVC	1000	45	WHITE, MATTE	C

1505F Coax - RG-59/U Type

1505F G8L1000	#21 GIFHDL DPE DBLB PVC	1000	45	ORANGE, MATTE	C
1505F Z4B1000	#21 GIFHDL DPE DBLB PVC	1000	45	VIO Z4B	

C = CRATE REEL PUT-UP.

Revision Number: 7 Revision Date: 07-13-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.