

Specification:


Material:

1. Housing : PC 1250Y UL 94V-2, Ivory color.
2. Dust Cover : ABS UL 94V-0, Black color.
3. Plastic Holder : ABS UL 94V-0, Ivory color.
4. Clip : STAINLESS.


Adaptor Type :

- a. MTRJ Simplex Type , Multimode.

Parameter	Condition	Multimode	Singlemode
Insertion loss	$\lambda=1300\text{nm}$	<0.3dB	<0.2dB
Operation Temperature	-20~70°C	0.2dB	0.2dB
Durability Temperature	500 cycles	0.2dB	0.2dB
Cycle	-20~80°C	0.2dB	0.2dB
Tensile Strength	10kgf	0.2dB	0.2dB



SUGGESTED PANEL CUTOUT



TOLERANCE							
INCHES	M/M						
. X	.015	.30	TNT Tri-Net Technology, Inc. http://www.trinetusa.com				
. XX	.010	.10					
. XXX	.005	.05					
DRAWN BY		Jack	SCALE	1/1		REV	A
CHECK BY		Debird	UNIT	MM		DWG NO.	
APPD BY		Peter	SHEET	1/1	TITLE		
			DATE	10/12/04	MTRJ-MTRJ MM ADAPTER		
			PART NO.		071-MTRJ-XX		