



05GE-XX-A-XX

COLOR: BK, RD, YL, GN, BL, GY, WH.

LENGTH UNIT: FT

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	————	1
ORANGE	2	————	2
WHITE/GREEN	3	————	3
BLUE	4	————	4
WHITE/BLUE	5	————	5
GREEN	6	————	6
WHITE/BROWN	7	————	7
BROWN	8	————	8
接线方式	568B	————	568B

REMARK:

1. CABLE: UTP CAT. 6 CABLE. 4P*24AWG (7/0. 205) (BARE COPPER. INSULATION: HD-PE. OD: 0.98 ± 0.05mm) +CROSS+OUTER JACKET: GPVC, OD: 6.2 ± 0.2mm. TNT P/N: 06G-R4P-T24-XX.
2. CONN. : P1, P2 8P8C PLUG, SHORT BODY, DOUBLE LAY, GOLD PLATED 50u". TNT P/N: 05BR(060-F88-T50-SB-STG)
3. ALL HOOD: MOLDING 60P PVC.
4. CABLE ASS'Y MUST PASS CONTINUITY TEST.
5. MOLD NO: TNT-88-07(14).



TOLERANCE		INCHES		M/M	TNT Tri-Net Technology, Inc.				
.X	.015			.30	http://www.trinetusa.com				
.XX	.010			.10	SCALE	NONE		REV	A
.XXX	.005			.05	UNIT	MM			
DRAWN BY	WENDI				SHEET	1/2	DWG NO.		
					DATE	06/06/06			
CHECK BY					TITLE				
					8P8C PLUG/8P8C PLUG				
APPD BY					PART NO.				
					05GE-XX-A-XX				