



L	T
L<=3FT	+50/-50mm
3FT<L<=15FT	+100/-100mm
15FT<L<=30FT	+150/-150mm
L>30FT	+200/-200mm

05GR-XX-A-XX
 COLOR:BLACK,RED,YELLOW,
 GREEN,BLUE,GRAY,WHITE.
 LENGTH UNIT:FT

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	———	1
ORANGE	2	———	2
WHITE/GREEN	3	———	3
BLUE	4	———	4
WHITE/BLUE	5	———	5
GREEN	6	———	6
WHITE/BROWN	7	———	7
BROWN	8	———	8
WIRING	568B	———	568B

- REMARK:
- CABLE:UTP CAT.6 CABLE.4P*24AWG(7/0.205)(BARE COPPER.INSULATION:HD-PE.OD:0.98±0.05mm) +CROSS+OUTER JACKET:PVC,OD:6.2±0.2mm. TNT P/N:06G-R4P-T24-XX.
 - CONN.:P1,P2 8P8C MODULAR,,SHORT BODY, DOUBLE LAY,GOLD PLATED 50u". TNT P/N:05BR(060-F88-T50-SB-STG)
 - ALL HOOD:MOLDING 60P PVC.
 - CABLE ASS'Y MUST PASS CONTINUITY TEST.
 - MOLD NO:TNT-88-07(14).



TOLERANCE			Tri-Net Technology, Inc.			
INCHES	M/M		http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE	REV	A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/2	DWG NO.	
DRAWN BY			DATE	04/14/06		
CHECK BY			TITLE 8P8C PLUG/8P8C PLUG			
APPD BY			PART NO. 05GR-XX-A-XX			