



L	T
L<6FT	+30/-30mm
6FT<=L<15FT	+50/-50mm
15FT<=L<50FT	+150/-150mm
L>=50FT	+300/-300mm

PN: 05WE-XX-A-XX
 COLOR: BK, RD, YL, GN, BL, GY, WH.
 LENGTH UNIT: FT.

WIRING LIST

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	————	1
ORANGE	2	————	2
WHITE/GREEN	3	————	3
BLUE	4	————	4
WHITE/BLUE	5	————	5
GREEN	6	————	6
WHITE/BROWN	7	————	7
BROWN	8	————	8

REMARK:

- CABLE: CAT.6 UTP 4P*24AWG(1/0.565)(BARE COPPER INSULATION: PE.)+FILLER+OUTER JACKET: PVC, OD=5.2±0.2MM (TNT P/N: BEL-7883A-XX)
- CONN.: P1, P2 8P8C MODULAR,, SHORT BODY, DOUBLE LAY, GOLD PLATED 50u".
TNT P/N: 05BR(060-F88-T50-SB-STG)
- ALL HOOD: MOLDING 60P PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- OVERMOLS MOLD NO: TNT-88-04



TOLERANCE			Tri-Net Technology, Inc.			
INCHES	M/M		http://www.trinetusa.com			
.X	.015	.30	SCALE	NONE	REV	A
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/1	DWG NO.	
DRAWN BY	MIKE		DATE	05/04/06		
CHECK BY			TITLE 8P8C TO 8P8C			
APPD BY			PART NO. 05WE-XX-A-XX			