



**WIRING LIST**

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	————	1
ORANGE	2	————	2
WHITE/GREEN	3	————	3
BLUE	4	————	4
WHITE/BLUE	5	————	5
GREEN	6	————	6
WHITE/BROWN	7	————	7
BROWN	8	————	8

**NOTE:**

- CAT. 6 UTP 24AWG\*4P (7/0.205, BARE COPPER INSULATION:PE)  
+CORSS JACKET:GRAY (TNT-GY-02) PVC, OD=6.2±0.2MM  
(TNT P/N: 06G-R4P-T24-GY)
- CONN. :P1:8P8C PLUG, LONG BODY, SINGLE LAY, GOLD PLATED  
50u", TNT P/N:05GD(060-R88-T50-C6E)  
P2:8P8C JACK INSULATION:BLACK PIN G/F  
(TNT P/N:C-8P8CF-BK-01)
- ASS'Y BOOT:Ø6.2mm (TNT P/N: 060-BOOT-SR3-GY)
- ALL HOOD: MOLDED GRAY (TNT-GY-02) PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- P1 MOLD NO:TNT-BOOT-SR3;P2 MOLD NO:TNT-88F-01



TOLERANCE			<b>Tri-Net Technology, Inc.</b> <a href="http://www.trinetusa.com">http://www.trinetusa.com</a>				
INCHES	M/M						
.X	.015	.30	SCALE	NONE		REV	B
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET	1/1	DWG NO.		
DRAWN BY			DATE	02/21/05	TITLE		
CHECK BY			8P8C PLUG TO 8P8C JACK				
APPD BY			PART NO. 086-C6-006				