



REMARK:
NOTES:

- CABLE:UTP CAT.6 CABLE.4P*24AWG(7/0.203)(STRANDED BARE COPPER. INSULATION:HD-PE.OD:0.95±0.05MM)+OUTER JACKET: BLUE PVC.OD:6.2±0.15MM.P/N:06G-R4P-T24-BL-TPL.
- CONN.: P1,P2: 8P8C PLUG, LONG BODY, DUBLE LAY. GOLD PLATED 3U", TWO PARTS.P/N:060-R88-T3-24AWG.
- ALL HOOD MOLDED BLUE 60P PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- MOLD NO: TNT-88-18, TNT-88-37.



A	INITIAL RELEASE		06/29/11	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES		M/M		Tri-Net Technology, Inc. Total Network Telesis U.S.A.
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		SCALE NONE
DRAWN BY		Tiger		UNIT MM
CHECK BY				REV A
APPD BY				SHEET 1/1
				DATE 06/29/11
				DWG NO.
				TITLE
				8P8C PLUG(90°,RIGHT) TO 8P8C PLUG(180°)
				PART NO.
				CAT6-UTP-RIGHT-XX