



	A06-KA22P	A06-KA42P
PCs Supported:	2	4
Enclosure:	Plastic	Plastic
Compatible Standards:	IEEE 1284 Parallel Port Communication Standard	IEEE 1284 Parallel Port Communication Standard
Dimensions:	(H) 3.75 in. (9.5 cm) x (W) 7.0 in. (17.8 cm) x (D) 1.25 in. (3.2 cm)	(H) 3.75 in. (9.5 cm) x (W) 7.0 in. (17.8 cm) x (D) 1.25 in. (3.2 cm)
Weight:	202 g (7.1 OZ.)	202 g (7.1 OZ.)
Operating Temp:	32°F to 104° (0° to 40°C)	32°F to 104° (0° to 40°C)
Storage Temp:	14° to 122°F (-10° to 50°C)	14° to 122°F (-10° to 50°C)
Humidity:	0-95% RH, non-condensing	0-95% RH, non-condensing
Electrical:	Input Voltage: 9VDC Max Input Current: 600mA Max Power Consumption: 5.4W Max Heat Dissipation: 0.31 BTU/min	Input Voltage: 9VDC Max Input Current: 600mA Max Power Consumption: 5.4W Max Heat Dissipation: 0.31 BTU/min
Warranty:	18 Months	18 Months
Note:	Specifications are subject to change without notice.	Specifications are subject to change without notice.