



	A09-KE102P	A09-KE104P
PCs Supported:	2	4
Keyboard/Mouse Emulation:	PS/2	PS/2
Monitors Supported:	VGA SVGA, MultiSync, and LCD (with use of adapter cable)	VGA SVGA, MultiSync, and LCD (with use of adapter cable)
Max. Resolution:	2048 x 1536	2048 x 1536
Keyboard Input:	6-pin miniDIN (PS/2)	6-pin miniDIN (PS/2)
Keyboard output:	6-pin miniDIN (PS/2)	6-pin miniDIN (PS/2)
Mouse Input:	6-pin miniDIN (PS/2)	6-pin miniDIN (PS/2)
Mouse output:	6-pin miniDIN (PS/2)	6-pin miniDIN (PS/2)
VGA Port :	15-pin HDDB type	15-pin HDDB type
LED Indicators:	2xGreen @Top	4xGreen @Top
Enclosure:	Metal	Metal
Power:	By PS/2 Keyboard port or optional DC9V. 600mA adapter with center pin positive polarity	By PS/2 Keyboard port or optional DC9V. 600mA adapter with center pin positive polarity
Dimensions:	(H) 2.9 x (W) 17.8 x (D) 9.6 cm	(H) 2.9 x (W) 17.8 x (D) 9.6 cm
Weight:	0.26 KG	0.26 KG
Operating Temp:	32°F to 104° (0°to 40°C)	32°F to 104° (0°to 40°C)
Storage Temp:	-4°to 140°F (-20° to 60°C)	-4°to 140°F (-20° to 60°C)
Humidity:	0-80% RH, non-condensing	0-80% RH, non-condensing
Warranty:	18 Months	18 Months
Note:	Specifications are subject to change without notice.	Specifications are subject to change without notice.