


| | |
|-------|-------|
| P1 | P2 |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 1 | 1 |
| 1 | 1 |
| 1 | 1 |
| 1 | 1 |
| 18 | 18 |
| 19 | 19 |
| SHELL | SHELL |



NOTE:

- 1.WIRE: 30AWG WIRE HARNESS L=20mm.
- 2.CONN.: P1&P2: HDMI 19 FEMALE,PIN AND SHELL PLATED GOLD,TNT PN:C-HDMI19F-01G..
- 3.ALL HOOD: MOLD PVC: 25P BLACK.
- 4.TEST: INSULATION RESISTANCE 10M OHM MIN AT DC500V.



| TOLERANCE | | | TNT Tri-Net Technology, Inc. http://www.trinetusa.com | |
|-----------|-------------|-----|---|----------|
| INCHES | M/M | | SCALE | NONE |
| .X | .015 | .30 | UNIT | MM |
| .XX | .010 | .10 | SHEET | 1/1 |
| .XXX | .005 | .05 | DATE | 01/10/06 |
| DRAWN BY | <i>myle</i> | | REV A | |
| CHECK BY | <i>lamp</i> | | DWG NO. | |
| APPD BY | <i>to</i> | | TITLE HDMI-FF-02 | |
| | | | PART NO. E11-HDMI-FF-02 | |