



DVI-A

DVI-A



DVI-A	DVI-A	CABLE FUNCTION
PIN 6	PIN 6	DDC CLOCK
PIN 7	PIN 7	DDC DATA
PIN 8	PIN 8	VERTICAL SYNC
PIN 14	PIN 14	+5V POWER
PIN 15	PIN 15	GND+5V,HV SYNC
PIN 16	PIN 16	HOT PLUG DETECT
C1	C1	ANALOG RED
C2	C2	ANALOG GREEN
C3	C3	ANALOG BLUE
C4	C4	HORIZONTAL SYNC
C5	C5	ANALOG GROUND
SHIELD	SHIELD	GROUND

ELECTRONIC TEST:
 1.100% OPEN AND SHORT TEST
 2.CONTACT RESISTANCE: $1 \pm 2 \Omega$
 3.INSULATION RESISTANCE: >50M Ω 10ms AT DC 500V



NO.	DESCRIPTION	UNIT	QTY
4	UL20276 3C*UL1354+1P*30#+5C*30#+AL+D+B DD6.5 MICROSOFT WHITE		
3	THUMB SCREW #4-40	PCS	4
2	PVC MOLDING WITH METAL CAN SHIELDED,MICROSOFT WHITE	CM	C
1	DVI-A MALE CONNECTOR		

TOLERANCE				DWG NO. DVI-012		TNT Tri-Net Technology		
SELECT	1	2	3	DR:	TITLE:	DVI-A TO DVI-A CABLE		
0.000 +/-	0.05	0.1	0.15	CHKD:	PART NO.:	E08-AM-AM-XX		
0.00 +/-	0.1	0.15	0.25	SALES:	CUSTOMER NAME:			
0.0 +/-	0.15	0.3	0.5	APPR:	CUSTOMER P/N:	UNIT	SCALE	REV.
0 +/-	0.25	0.5	1.0			MM	NONE	A
MATERIAL:								