



DV-D

VGA



DV-A	VGA	CABLE FUNCTION
PIN 6	PIN 15	DDC CLOCK
PIN 7	PIN 12	DDC DATA
PIN 8	PIN 14	VERTICAL SYNC
PIN 14.16	PIN 9	POWER +5V/HOT PLUG DETECT
PIN 15	PIN 5.10	GROUND(+5V &HV SYNC)
SHIELD	SHIELD	GROUND

TEST CONDITION:

1. 100% OPEN/SHORT TEST.
2. CONTACT RESISTANCE: 2Ω.
3. INSULATION RESISTANCE: 50MΩ.
DC 300V AT 10ms.

NO.	DESCRIPTION	PART NO.	QTY	MATERIAL:	APPR:	DWG NO.:	TITLE:	UNIT	SCALE	REV.
7	HDD15M CONNECTOR:G/F BLACK.	7CHDS1510200010 (GHD15-MSY101-OK)	1			SDC-4002	Tri-Net Technology	mm	1/1	1
6	PVC MOLDING HOOD WITH COPPER 360° FOIL SHIELDED, MICROSOFT WHITE IN COLOR	WZ000015								
5	THUMB SCREW: #4-40UNC.	WE020047	2							
4	UL20276 3C*UL1354+1P*30#+5C*30#+AL+D+B,OD:7.5, MICROSOFT WHITE IN COLOR.	WF040063*0180								
3	THUMB SCREW: #4-40UNC.	WE020083*	2							
2	PVC MOLDING WITH METAL CAN SHIELDED,MICROSOFT WHITE IN COLOR.	WZ000015								
1	DV-D 18PIN MALE,HELIX(CONTACT:GOLD PLATED 15U").	7CDVS2410200101	1							

R050202A