



Power adapter
 Input: AC110-240V
 Output: DC5V, 2.0A

Specifications:

1. It can extend VGA video and audio up to 1000feet/300m(1024x768-3db)
2. Provides a VGA interface on the transmitter for using locally
3. Use a piece of UTP cable (CAT5, CAT5E, CAT6) to connect local and remote units.
4. Supports VGA video extending, and bandwidth as high as 350M
5. Supports video resolution between 640X480 to 1920X1440, and perfectly supports high-clear TV resolution
6. Transmit VGA video and audio signal without delay
7. No need a driver and easy installation
8. perfect anti-jamming and satisfy any kinds of harsh environment
9. Power Consumption: 10 Watts (max)
10. Power Supply: DC 5V, 2.0A
11. Dimensions:
12. Shell Color: White

| | | | | |
|----------|-----------------------|----------|---|----------|
| A | INITIAL RELEASE | | 05/25/09 | |
| REV | DESCRIPTION OF CHANGE | | | DATE |
| | TOLERANCE INCHES | M/M | Tri-Net Technology, Inc. http://www.trinetusa.com | |
| .X | .015 | .30 | SCALE | NONE |
| .XX | .010 | .10 | UNIT | MM |
| .XXX | .005 | .05 | DATE | 05/25/09 |
| DRAWN BY | LEO | SHEET | DWG NO. | |
| CHECK BY | | TITLE | VGA UTP Extender With Audio 110 Type Face Plate RECEIVER ONLY | |
| APPD BY | | PART NO. | R02-EXT-35A-RX-FP | |

