



Power adapter
 Input: AC110-240V
 Output: DC5V, 2.0A

Specifications:

1. It can extend VGA video and RS-232 up to 1000feet/300m(1024x768-3db)
2. Provides a VGA interface on the transmitter for using locally
3. Use a piece of UTP cable (CAT5, CAT5E, CAT6) to connect local and remote units.
4. Supports VGA video extending, and bandwidth as high as 350M
5. Supports video resolution between 640X480 to 1920X1440, and perfectly supports high-clear TV resolution
6. Transmit VGA video and audio signal without delay
7. No need a driver and easy installation
8. perfect anti-jamming and satisfy any kinds of harsh environment
9. Power Consumption: 10 Watts (max)
10. Power Supply: DC 5V, 2.0A
11. Dimensions:
12. Shell Color: White

A	INITIAL RELEASE		03/25/09	
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE INCHES		M/M	TNT Tri-Net Technology, Inc. http://www.trinetusa.com	
.X	.015	.30	SCALE	NONE
.XX	.010	.10	UNIT	MM
.XXX	.005	.05	DATE	03/25/09
DRAWN BY	LEO	SHEET	DWG NO.	
CHECK BY		TITLE VGA UTP Extender With RS232 110 Type Face Plate RECEIVER ONLY		
APPD BY		PART NO. R02-EXT-RS-RX-FP		

