



P/N: 800-DLC-DST-S-XX-YL



| XX      | YY     |
|---------|--------|
| XX ≤ 1M | ±50mm  |
| XX > 1M | ±100mm |



**Specification:**

- |                   |  |                 |              |
|-------------------|--|-----------------|--------------|
| 1. Connector A    | LC/PC S/M  | P/N: 880-LC-S-C | BOOT:WHITE   |
| 2. Connector B    | ST/PC S/M  | P/N: 880-ST-S-C | BOOT:YELLOW  |
| 3. Cable Type     | Duplex ø1.8mm  | 9.0/125um       | Single-Mode. |
| 4. Length         | XX(UNIT:METER)   |                 |              |
| 5. Jacket Color   | YELLOW.  |                 |              |
| 6. Insertion Loss | <0.40 dB   |                 |              |
| 7. Return Loss    | >50 dB   |                 |              |
| 8. PACKING        | EACH CABLE IN A TNT PRINTED ZIP-LOCK POLY-BAG(08*8"*10").<br>BAR CODE LABEL TO BE ADHERED ON POLY-BAG. |                 |              |

| TOLERANCE |      |     | <b>TNT</b> Tri-Net Technology   |          |              |     |
|-----------|------|-----|---------------------------------|----------|--------------|-----|
| INCHES    | M/M  |     |                                 |          |              |     |
| .X        | .015 | .30 | TITLE: Single-Mode Duplex LC-ST |          |              |     |
| .XX       | .010 | .10 | PART NO.: 800-DLC-DST-S-XX-YL   |          |              |     |
| .XXX      | .005 | .05 |                                 |          |              |     |
| DRAWN BY  |      |     | SCALE                           | NONE     | DRAWING NO.: | REV |
| CHECK BY  |      |     | UNIT                            | MM       | TNT-0063     | A   |
| APPD BY   |      |     | DATE                            | 02/09/11 |              |     |