

L	T
L ≤ 3FT	+50/-50mm
3FT < L ≤ 15FT	+100/-100mm
15FT < L ≤ 30FT	+150/-150mm
L > 30FT	+200/-200mm

KEEP EACH PAIR TWIST UNTIL END OF EACH SLOT IN 110 PLUG.

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	3	—	3
ORANGE	6	—	4
WHITE/GREEN	1	—	5
BLUE	4	—	2
WHITE/BLUE	5	—	1
GREEN	2	—	6
WHITE/BROWN	7	—	7
BROWN	8	—	8
WIRING	568A	—	568A


097-845-A-XX-YY-05BR

COLOR: BLACK, RED, YELLOW,
GREEN, BLUE, GRAY, WHITE.
Length unit: FT

APPROVED BY _____
 COMPANY: _____
 PURCHASING/ENGINEER: _____
 DATE: _____

REMARK:

- CABLE: UTP CAT.5e CABLE. 4P*24AWG(7/0.205)(BARE COPPER.INSULATION:HD-PE.OD:0.98±0.05mm) + OUTER JACKET:PVC,OD:5.6±0.2mm. P/N: 06F-R4P-T24-XX.
- CONN.: P1,8P8C MODULAR,,SHORT BODY,DOUBLE LAY,GOLD PLATED 50u". P/N:05BR(060-F88-T50-SB-STG) P2,4 PAIR 110 PATCH PLUG,ASSEMBLY,TRANSPARENT BODY, P/N:094-4
- KEEP EACH PAIR TWIST UNTIL END OF EACH SLOT IN 110 PLUG.
- HOOD:MOLDING 90P PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- MOLD NO:88-03.



REV	TOLERANCE INCHES	M/M	INITIAL RELEASE	DESCRIPTION OF CHANGE	DATE
A	.X	.015	.30		11/01/07
	.XX	.010	.10		
	.XXX	.005	.05		
DRAWN BY		Walt		SHEET 1/1	
CHECK BY				DATE 11/01/07	
APPD BY				DWG NO.	
PART NO.			8P8C RJ45 TO 4pair 110 patch cords		
097-845-E-XX-YY-05BR					