

NOTES:

1. ALL DIMENSIONS ARE "MM".

2. ELECTRICAL:

UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
 INSULATION RESISTANCE: 500 MEGOHMS.
 TERMINATION RESISTANCE: 35 MILLIOHMS MAX AFTER ENVIRONMENTAL TESTING.

3. MECHANICAL:


CABLE-TO-PLUG TENSILE STRENGTH: 20 lbs (89N) MIN.
 DURABILITY: 200 MATING CYCLES.

4. MATERIAL & FINISH:

HOUSING: POLYCARBONATE, VL94V-2.
 COLOR: CLEAR (CUSTOM COLOR AVAILABLE).
 CONTACT: HIGH STRENGTH COPPER ALLOY.
 GOLD PLATING OVER 100 MICRO INCH NICKEL.
 CONDUCTOR: STRANDED, 24, 26, 28, AWG.



NOTE TOL: $\pm 0.1\text{m/m}$

	DSGN	SUNNY	07.DEC.95	ITEM NO:	MP4P4C-50-1-1-N
	CHK			PART NUMBER	060-F44-T-6
UNIT	m/m	APPR			
SCALE	4/1				
DWG NO:					

TNT Tri-Net Technology / U.S.A.