



NOTES:

1. ALL DIMENSIONS ARE "MM".
2. ELECTRICAL:
 UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
 INSULATION RESISTANCE: 500 MEGOHMS.
 TERMINATION RESISTANCE: 35 MILLIOHMS MAX AFTER ENVIRONMENTAL TESTING.
3. MECHANICAL:
 CABLE-TO-PLUG TENSILE STRENGTH: 20 lbs (89N) MIN.
 DURABILITY: 200 MATING CYCLES.
4. MATERIAL & FINISH:
 HOUSING: POLYCARBONATE, VL94V-2.
 COLOR: CLEAR (CUSTOM COLOR AVAILABLE).
 CONTACT: HIGH STRENGTH COPPER ALLOY.
 GOLD PLATING OVER 100 MICRO INCH NICKEL.
 CONDUCTOR: STRANDED. 24. 26. 28. AWG.

NOTE TOL: ±0.1m/m



 UNIT m/m SCALE 4/1 DWG NO:	DSGN	SUNNY	07.DEC.95	ITEM NO:	MP6P4C-50-1-1-N
	CHK			PART NUMBER	060-F64-T-6
	APPR			 Tri-Net Technology / U.S.A.	