

A

B

XX	± YY
<915mm (3FT)	± ²⁰ ₁₀ mm
≥915mm (3FT)	± ⁴⁰ ₃₀ mm


STRAIGHT

A B

1 BLUE	_____	1 BLUE
2 ORANGE	_____	2 ORANGE
3 GREEN	_____	3 GREEN
4 BROWN	_____	4 BROWN
5 SLATE	_____	5 SLATE
6 WHITE	_____	6 WHITE
7 RED	_____	7 RED
8 BLACK	_____	8 BLACK
9 YELLOW	_____	9 YELLOW
10 VIOLET	_____	10 VIOLET
11 ROSE	_____	11 ROSE
12 AQUA	_____	12 AQUA

Specification:

- | | | |
|-------------------|------------------------|----------------|
| 1. Connector A | MTP 12CROE | M/M |
| 2. Connector B | MTP 12CROE | M/M |
| 3. Cable Type | 12 FIBERS RIBBON CABLE | M/M 62.5/125um |
| 4. Length | UNIT: (XX) METER | |
| 5. Jacket Color | ORANGE | |
| 6. Insertion Loss | <0.70 dB | |
| 7. RETURN LOSS | >25.0 dB | |

				02/01/08	
REV	DESCRIPTION OF CHANGE			DATE	
TOLERANCE		M/M		 Tri-Net Technology, Inc. http://www.trinetusa.com	
INCHES					
.X	.015	.30			
.XX	.010	.10		SCALE	NONE
.XXX	.005	.05		UNIT	MM
DRAWN BY		starl		SHEET	1/1
CHECK BY				DATE	02/01/08
APPD BY				TITLE	MTP-MTP Female 62.5/125u Ribbon Patchcords
				PART NO.	898-MTP-MTP-M-XX

