



L	T
L ≤ 3FT	+50/-50mm
3FT < L ≤ 15FT	+100/-100mm
15FT < L ≤ 30FT	+150/-150mm
L > 30FT	+200/-200mm

APPROVED BY _____

COMPANY: _____

PURCHASING/ENGINEER: _____

DATE: _____

05BF-XX-A-BL
 COLOR: BL: BLUE.
 LENGTH UNIT: FT.

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	———	1
ORANGE	2	———	2
WHITE/GREEN	3	———	3
BLUE	4	———	4
WHITE/BLUE	5	———	5
GREEN	6	———	6
WHITE/BROWN	7	———	7
BROWN	8	———	8

NOTE:

- CABLE: UTP CAT.5E CABLE. 4P*28AWG(7/0.12)(BARE COPPER. INSULATION: HD-PE. OD: 0.6±0.03mm)
 + OUTER JACKET: BLUE(BL-02) PVC, OD: 3.5±0.15mm.
- CONN.: P1, P2 8P8C MODULAR, SHORT BODY, SINGLE LAY, GOLD PLATED 50u".
- ALL HOOD: MOLDING 90P BLUE(BL-02) PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- MOLD NO.: 88-21.

A	INITIAL RELEASE		12/08/07		
REV	DESCRIPTION OF CHANGE		DATE		
TOLERANCE INCHES		M/M	Tri-Net Technology, Inc. http://www.trinetusa.com		
.X	.015	.30			
.XX	.010	.10			
.XXX	.005	.05	SCALE	NONE	REV A
			UNIT	MM	
DRAWN BY	Carl		SHEET	1/1	DWG NO.
			DATE	12/08/07	
CHECK BY			TITLE 8P8C TO 8P8C		
APPD BY			PART NO. 05BF-XX-A-BL		

