


PIN OUT	
P1 _____	P2 _____
1 _____	8 _____
2 _____	3 _____
3 _____	2 _____
4 _____	20 _____
5 _____	7 _____
6 _____	6 _____
7 _____	4 _____
8 _____	5 _____
9 _____	22 _____
SHELL _____	SHELL _____

NOTE:

1. WIRE: 26AWG, UL1061 + CSA.
2. CONNECTOR: P1: D-SUB 9PIN MALE, SOLDER TYPE, GOLD FLASH CONTACTS.  
P2: D-SUB 25PIN FEMALE, SOLDER TYPE, GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. HOOD: MOLDED BEIGE(CTG-401) PVC.
6. PACKING: 4PCS HEX. NUTS (5 X 5.5mm, #4-40 UNC) IN A PE POLY-BAG, SEALED, HEX. NUTS AND AN ADAPTER IN A CLEAR ZIP-LOCK POLY-BAG TOGETHER. BAR CODE LABEL(PINK BACKGROUND WITH BLACK LETTERS, CODE: 39) TO BE STAMPED ON POLY-BAG TO READ:

Molded Type Adapter  
DB25 Female to DB9 Male




A12-25F-9M  
TRI-NET TECHNOLOGY INC.



0

S

DRAWING APPROVED _____		DATE: _____	
SAMPLE APPROVED PER _____		DRAWING SPECIFICATIONS _____	
PROPRIETARY & CONFIDENTIAL. THIS DOCUMENT MAY NOT BE COPIED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF TNT.			
$\varnothing$	mm	TITLE	
SCALE	NONE	DB9 MALE TO DB25 FEMALE	
SHEET	1/1	CUS. NAME	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED		CUS. P/N	ENG. _____ DATE _____
.X ±	0.2	A12-25F-9M	CHECKED _____ DATE _____
.XXX ±	ANGLES ±	PART NO.	APPROVED _____ DATE _____
REV. $\varnothing$	CUS. REV A	P9907024-E	